

# Modeling with Ontologies and Rules

**Pascal Hitzler**

DaSe Lab for Data Semantics  
Wright State University, Dayton, OH  
<http://www.pascal-hitzler.de>



## Part II

# Ontology Design Patterns


**NSF effort for the earth sciences**

**Goal:**

**To transform the conduct of research in the geosciences by developing IT solutions for the integration of information and data in the geosciences.**

**How this is going to be done is still in the making.**


**Semantic Technologies have been part of the mix from the start.**



**[Berg-Cross, ..., Hitzler et al., GIBDa 2012]**

## EarthCube requires


- information integration
- interoperability
- conceptual modeling
- intelligent search
- data-model intercomparison
- data publishing support



## Semantic Web studies

- information integration
- interoperability
- conceptual modeling
- intelligent search
- data-model intercomparison
- data publishing support





[Joshi, Jain, Hitzler et al. ODBASE 2012]

# Ontological commitments



- |  |     |  |     |
|--|-----|--|-----|
| $a:\text{flowsInto} \sqsubseteq a:\text{IsConnected}$  | (1) | $b:\text{flowsInto} \sqsubseteq b:\text{IsConnected}$                          | (6) |
| $a:\text{IrrigationCanal} \sqsubseteq a:\text{Canal}$  | (2) | $b:\text{Canal} \sqsubseteq (\geq 2 b:\text{IsConnected}.b:\text{Waterbody})$  | (7) |
| $\exists a:\text{flowsInto}.a:\text{AgriculturalField} \sqsubseteq a:\text{IrrigationCanal}$ | (3) | $b:\text{IrrigationCanal} \equiv (=1 b:\text{IsConnected}.b:\text{Waterbody})$ |     |
| $a:\text{Waterbody} \sqcap a:\text{Land} \sqsubseteq \perp$                                  | (4) | $\sqcap (=1 b:\text{flowsInto}.b:\text{AgriculturalField})$                    | (8) |
| $a:\text{AgriculturalField} \sqsubseteq a:\text{Land}$                                       | (5) |  |     |


**Two ontologies.**

**Left: transportation domain**

**Right: agriculture domain**

**We cannot simply equate  $a:\text{Canal}$  and  $b:\text{Canal}$  !**


“Nancy Pelosi voted in favor of the Health Care Bill.”



- **Bottom-up homogenization of data representation.**
- **Avoidance of strong ontological commitments.**
- **Avoidance of standardization.**
- **Well thought-out patterns can be very strong and versatile, thus serve many needs.**

**We are currently establishing many geo-patterns in a series of hands-on workshops, the GeoVoCamps, see <http://vocamp.org/>**






**“Horizontal” alignment via patterns**

# Patterns TOC




- **Semantic Trajectories**
- **Biodiversity**
- **Map Scaling**
- **Part-of Relationships**

# Semantic Trajectories



[Hu, Janowicz, Carral, Scheider, Kuhn, Berg-Cross, Hitzler, Dean, COSIT2013]

# Semantic Trajectories



# Semantics in OWL



$$\begin{aligned} \text{Fix} \sqsubseteq \exists \text{atTime}. \text{OWL-Time:Temporal Thing} \sqcap \exists \text{hasLocation}. \text{Position} \\ \sqcap \exists \text{hasFix}^- . \text{SemanticTrajectory} \end{aligned} \quad (1)$$

$$\text{Segment} \sqsubseteq \exists \text{startsFrom}. \text{Fix} \sqcap \exists \text{endsAt}. \text{Fix} \quad (2)$$

$$\top \sqsubseteq \leq 1 \text{startsFrom}. \top \quad (3)$$

$$\top \sqsubseteq \leq 1 \text{endsAt}. \top \quad (4)$$

$$\text{Segment} \sqsubseteq \exists \text{hasSegment}^- . \text{SemanticTrajectory} \quad (5)$$

$$\text{startsFrom}^- \circ \text{endsAt} \sqsubseteq \text{hasNext} \quad (6)$$

$$\text{hasNext} \sqsubseteq \text{hasSuccessor} \quad (7)$$

$$\text{hasSuccessor} \circ \text{hasSuccessor} \sqsubseteq \text{hasSuccessor} \quad (8)$$

$$\text{hasNext}^- \sqsubseteq \text{hasPrevious} \quad (9)$$

$$\text{hasSuccessor}^- \sqsubseteq \text{hasPredecessor} \quad (10)$$

$$Fix \sqcap \neg \exists endsAt.Segment \sqsubseteq StartingFix \quad (11)$$

$$Fix \sqcap \neg \exists startsFrom.Segment \sqsubseteq EndingFix \quad (12)$$

$$Segment \sqcap \exists startsFrom.StartingFix \sqsubseteq StartingSegment \quad (13)$$

$$Segment \sqcap \exists endsAt.EndingFix \sqsubseteq EndingSegment \quad (14)$$

$$SemanticTrajectory \sqsubseteq \exists hasSegment.Segment \quad (15)$$

$$hasSegment \circ startsFrom \sqsubseteq hasFix \quad (16)$$

$$hasSegment \circ endsAt \sqsubseteq hasFix \quad (17)$$

$$\exists hasSegment.Segment \sqsubseteq SemanticTrajectory \quad (18)$$

$$\exists hasSegment^- .SemanticTrajectory \sqsubseteq Segment \quad (19)$$

$$\exists hasFix.Segment \sqsubseteq SemanticTrajectory \quad (20)$$

$$\exists hasFix^- .SemanticTrajectory \sqsubseteq Fix \quad (21)$$

# Patterns TOC



- Semantic Trajectories
- **Biodiversity**
- Map Scaling
- Part-of Relationships

[ACM GIS 2012]

The pattern which we introduce is used for *type-count comparison* – we correspondingly call it the *type-count comparison pattern*. Syntactically, we write it as

$$R \equiv D \times D|_{C_1, \dots, C_n},$$

where  $R$  is a role name, and  $D$  and the  $C_i$  are concepts.

Intuitively, the semantics of this pattern is as follows: Two individuals  $x$  and  $y$  shall be connected by the role  $R$  if and only if  $x$  is contained in strictly more different classes  $C_i$  than  $y$ . E.g., say  $x$  is contained in  $C_1$  and  $C_5$  (but not in any other  $C_i$ , while  $y$  is contained in  $C_2$  (but not in any other  $C_j$ ), then we would like to infer  $R(x, y)$ . The notation using a vertical bar is borrowed from a very common mathematical notation used for restricting functions to subsets of their domains.



# Non-monotonicity



Consider the knowledge base consisting of the following statements.

$$R \equiv \top \times \top |_{C_1, C_2}$$
$$C_1(a)$$
$$C_2(a)$$
$$C_1(b)$$

From this knowledge base we would like to infer  $R(a, b)$ , since  $a$  is known to be contained in the two classes  $C_1$  and  $C_2$ , while  $b$  is only known to be contained in  $C_1$ .

However, now assume we add the axiom  $C_2(b)$  to the knowledge base. Under this new knowledge base, we would no longer infer  $R(a, b)$ , since both  $a$  and  $b$  are contained in two of the classes. Note that the *addition* of the axiom  $C_2(b)$  means that a previously drawn inference, namely  $R(a, b)$ , is no longer a valid inference. This observation shows that we are in fact considering a so-called *non-monotonic* semantics. Such non-monotonic semantics usually arise in the context of some kind of (local) world closure as discussed at the end of section 2.

In our formal semantics we will therefore have to reflect this, and introduce some non-monotonic semantic construct. We will discuss this further in section 3.3.

# Semantics

Table 2: Expansion of  $R \equiv D \times D|_{C_1, \dots, C_n}$

$$\text{Close}(C_i) \quad (1)$$

for all  $1 \leq i \leq n$ .

$$R \sqsubseteq D \times D \quad (2)$$

$$D \sqsubseteq N_{0,0} \quad (3)$$

$$N_{m-1,k} \sqcap \neg C_m \sqsubseteq N_{m,k} \quad (4)$$

$$N_{m-1,k} \sqcap C_m \sqsubseteq N_{m,k+1} \quad (5)$$

where all  $N_{i,j}$  are freshly introduced classes where  $m = 1, \dots, n$  and  $k = 1, \dots, m - 1$  for every  $m$ .

$$N_{n,i} \sqsubseteq \exists S_i. \text{Self} \quad (6)$$

where  $i = 0, \dots, n$ .

$$S_i \circ R \circ S_j \sqsubseteq R_{\text{typeCountViolation}} \quad (7)$$

for all  $i \leq j$  where  $j = 0, \dots, n$ .

$$S_i \circ U \circ S_j \sqsubseteq R \quad (8)$$

for all  $i > j$  where  $i = 1, \dots, n$ .

- Straightforward carrying over of circumscription to DLs:  
**undecidable for expressive DLs**  
[Bonatti, Lutz, Wolter, KR2006, JAIR 2009]

Unintuitive modeling: extensions of minimized predicates may contain unknown individuals

- Fixing the unintuitive aspect: allow only named individuals in extensions of minimized predicates  
**decidable even for very expressive DLs**  
we also have a tableaux algorithm  
[Sengupta, Krisnadhi, Hitzler, ISWC2011]

called *Grounded Circumscription*

- Use a knowledge base  $K$  as usual.
- Additionally, specify “circumscribed” (minimized) predicates.
- Among all models  $M$  of  $K$ , the circumscribed models (c-models) are those for which there is no model which is preferred over  $M$ .

A model  $J$  is *preferred over*  $M$  if

- a) they have the same domain of discourse
- b) constants have the same extensions in both models
- c) the  $J$ -extension of each minimized predicate is contained in its  $M$ -extension
- d) the  $J$ -extension of some minimized predicate is strictly contained in its  $M$ -extension

# Grounded Circumscription for DLs



- Use a knowledge base  $K$  as usual.
- Additionally, specify “circumscribed” (minimized) predicates.
- Among all models  $M$  of  $K$ , the circumscribed models (**gc-models**) are those for which there is no model which is preferred over  $M$  **and extensions of minimized predicates contain only named individuals.**

A model  $J$  is *preferred over*  $M$  if

- a) they have the same domain of discourse
- b) constants have the same extensions in both models
- c) the  $J$ -extension of each minimized predicate is contained in its  $M$ -extension
- d) the  $J$ -extension of some minimized predicate is strictly contained in its  $M$ -extension

# Circumscription vs. Grounded Circ.



- **Circumscription:**
  - minimization of roles leads to undecidability (for non-empty Tboxes)
- **Grounded Circumscription:**
  - Decidable even under role grounding for very expressive decidable DLs.
  - Complexity upper bound for satisfiability or for finding a gc-model is  $EXP^C$ , where C is the complexity of the underlying DL.

**We also have a tableaux algorithm for different reasoning tasks.**

# Example



`hasAuthor(paper1, author1)`

`hasAuthor(paper1, author2)`

`hasAuthor(paper2, author3)`

$\top \sqsubseteq \forall \text{hasAuthor. Author}$

**Both of**

$\neg \text{hasAuthor}(\text{paper1}, \text{author3})$   
 $(\leq 2 \text{ hasAuthor. Author})(\text{paper1})$

**are not logical consequences under classical DL semantics.**

**However, they are logical consequences when hasAuthor is minimized (using the UNA).**


# Patterns TOC



- Semantic Trajectories
- Biodiversity
- **Map Scaling**
- Part-of Relationships



# Cartographic Map Scaling



[Carral, Scheider, Janowicz, Vardeman, Krisnadhi, Hitzler, ESWC2013]

# Semantics in OWL



$$\text{sharesApplicationWith} \circ \text{sharesApplicationWith} \sqsubseteq \text{sharesApplicationWith} \quad (1)$$

$$\text{sharesApplicationWith}^- \sqsubseteq \text{sharesApplicationWith} \quad (2)$$

$$\text{Map} \sqsubseteq \exists \text{sharesApplicationWith}.\text{Self} \quad (3)$$

$$\top \sqsubseteq \leq 1 \text{hasScale}.\top \quad (4)$$

$$\text{hasScale}^- \sqsubseteq \text{getMap} \quad (5)$$

$$\top \sqsubseteq \leq 1(\text{getMap} \circ \text{sharesApplicationWith}).\top \quad (6)$$

$$\text{isConstituentOf} \circ \text{hasScale} \sqsubseteq \text{isScaled} \quad (7)$$

$$\text{isLargerThan} \circ \text{isLargerThan} \sqsubseteq \text{isLargerThan} \quad (8)$$

$$\exists(\text{isLargerThan} \sqcap \text{isLargerThan}^-).\top \sqsubseteq \perp \quad (9)$$

$$\text{isMoreGeneralThan} \circ \text{isMoreGeneralThan} \sqsubseteq \text{isMoreGeneralThan} \quad (10)$$

$$\exists(\text{isMoreGeneralThan} \sqcap \text{isMoreGeneralThan}^-).\top \sqsubseteq \perp \quad (11)$$

# Semantics in OWL



$$isCompatibleWith^- \sqsubseteq isCompatibleWith \quad (12)$$

$$ScaleLevel \sqsubseteq \exists isCompatibleWith.Self \quad (13)$$

$$ScaleLevel \sqsubseteq \exists hasLowerBound.xsd:float \quad (14)$$

$$ScaleLevel \sqsubseteq \exists hasUpperBound.xsd:float \quad (15)$$

$$\top \sqsubseteq \leq 1 hasLowerBound.\top \quad (16)$$

$$\top \sqsubseteq \leq 1 hasUpperBound.\top \quad (17)$$

$$\top \sqsubseteq \leq 1 isPresentedAs.\top \quad (18)$$

$$\top \sqsubseteq \leq 1 isScaled.\top \quad (19)$$

$$\top \sqsubseteq \leq 1 representsObject.\top \quad (20)$$

$$ScaledRep \sqsubseteq \exists isPresentedAs.GeometricRep \quad (21)$$

$$ScaledRep \sqsubseteq \exists isScaled.ScaleLevel \quad (22)$$

$$ScaledRep \sqsubseteq \exists representsObject.GeographicThing \quad (23)$$

$$isConstituentOf^- \circ representsObject \circ representsObject^- \sqsubseteq R_{aux} \quad (24)$$

$$\top \sqsubseteq \leq 1 (R_{aux} \sqcap isConstituentOf^-).\top \quad (25)$$

$sharesApplicationWith(m_x, m_y) \wedge hasScale(s_y, m_y) \wedge hasScale(s_x, m_x)$   
 $\wedge isLargerThan(s_x, s_y) \wedge$   
 $isConstituentOf(m_x, sr_x) \wedge isConstituentOf(m_y, sr_y) \wedge$   
 $representsObject(sr_x, g) \wedge representsObject(sr_y, g) \wedge$   
 $isPresentedAs(sr_x, grr_x) \wedge isPresentedAs(sr_y, grr_y) \wedge$   
 $isMoreGeneralThan(grr_x, grr_y) \rightarrow \perp(m_x)$

This rule enforces that the ontology becomes inconsistent if

- there exist maps  $m_1$  and  $m_2$  belonging to the same application with scales  $s_1$  and  $s_2$ ,
- scale  $s_1$  is larger than scale  $s_2$ ,
- maps  $m_1$  and  $m_2$  contain scaled representations  $sr_1$  and  $sr_2$  that represent the same geographic thing  $g$ , and
- the geographic representation record  $grr_1$  for  $sr_1$  is more general than the one for  $sr_2$ , namely  $grr_2$ .

# Semantics in OWL



$sharesApplicationWith(m_x, m_y) \wedge hasScale(s_y, m_y) \wedge hasScale(s_x, m_x)$   
 $\wedge isLargerThan(s_x, s_y) \wedge$   
 $isConstituentOf(m_x, sr_x) \wedge isConstituentOf(m_y, sr_y) \wedge$   
 $representsObject(sr_x, g) \wedge representsObject(sr_y, g) \wedge$   
 $isPresentedAs(sr_x, grr_x) \wedge isPresentedAs(sr_y, grr_y) \wedge$   
 $isMoreGeneralThan(grr_x, grr_y) \rightarrow \perp(m_x)$

---

$hasScale^- \circ sharesApplicationWith \circ hasScale \sqsubseteq R_1$

$R_1 \sqcap isLargerThan \sqsubseteq R_2$

$isScaled \circ R_2 \circ isScaled \sqsubseteq R_3$

$isPresentedAs \circ isMoreGeneralThan^- \circ isPresentedAs^- \sqsubseteq R_4$

$representsObject \circ representsObject^- \sqsubseteq R_5$

$R_3 \sqcap R_4 \sqcap R_5 \sqsubseteq R_\perp$

$\exists R_\perp.T \sqsubseteq \perp$

# Patterns TOC



- Semantic Trajectories
- Biodiversity
- Map Scaling
- **Part-of Relationships**

**Content taken from**

**Morton E. Winston, Roger Chaffin, Douglas Herrmann, A Taxonomy of Part-Whole Relations, Cognitive Science 11, 417-444, 1987.**

**and the OWL modeling from**

**Prateek Jain, Pascal Hitzler, Kunal Verma, Peter Yeh, Amit Sheth, Moving beyond sameAs with PLATO: Parontology detection for Linked Data. In: Ethan V. Munson, Markus Strohmaier (Eds.): 23rd ACM Conference on Hypertext and Social Media, HT '12, Milwaukee, WI, USA, June 25-28, 2012. ACM, 2012, pp. 33-42.**

- the X is part of the Y
- X is partly Y
- X's are part of Y's
- X is a part of Y
- The parts of a Y include the Xs, the Zs, ...
  
- The head is part of the body
- Bicycles are partly aluminum
- Pistons are part of engines
- Dating is a part of adolescence
- The parts of a flower include the stamen, the petals, etc. ...
  
- “meronymic” relations (“meros” is greek for “part”)



# part-of: a possible view



One could think that part-of is a binary relation which is

- a strict partial ordering, i.e.
  - transitive  
If X part of Y, and Y part of Z. Then X part of Z.
  - irreflexive  
X is never part of X.
  - antisymmetric  
If X part of Y. Then Y is never part of X.

However, this view is problematic.

# Transitivity



**Simpson's finger is part of Simpson's hand.  
Simpson's hand is part of Simpson's body.  
Simpson's finger is part of Simpson's body.**

**This works, but the following doesn't:**

**Simpson's arm is part of Simpson.  
Simpson is part of the Philosophy Department.  
Hence(?) Simpson's arm is part of the Philosophy Department.**

**So when do we have transitivity?**

Distinguish 6 different types of meronymic relations:

1. component – integral object (pedal – bike)
2. member – collection (ship – fleet)
3. portion – mass (slice – pie)
4. stuff – object (steel – car)
5. feature – activity (paying – shopping)
6. place – area (Everglades – Florida)

# Dimensions of meronymic relations



## A type of part-of relationships

- **functional**  
Functional parts are restricted, by their function, in their spatial or temporal location.  
handle – cup
- **homeomerous**  
Homeomerous parts are the same kind of thing as their wholes.  
slice – pie  
but not tree – forest
- **separable**  
Separable parts can in principle be separated from the whole.  
handle – cup  
but not steel – bike

# Dimensions



Relation	Examples	Relation Elements		
		Functional	Homeomereous	Separable
Component/ Integral Object	handle-cup punchline-joke	+	-	+
Member/ Collection	tree-forest card-deck	-	-	+
Portion/Mass	slice-pie grain-salt	-	+	+
Stuff/Object	gin-martini steel-bike	-	-	-
Feature/Activity	paying-shopping dating-adolescence	+	-	-
Place/Area	Everglades-Florida oasis-desert	-	+	-

From Winston et al., A Taxonomy of Part-whole Relations,  
Cognitive Science 11, 417-444, 1987.

# Component – Integral Object



- A handle is part of a cup.
- Wheels are parts of cars.
- The refrigerator is part of the kitchen.
- Chapters are parts of books.
- A punchline is part of a joke.
- Belgium is part of NATO.
- Phonology is part of linguistics.
- The viola part in a symphony.

# Member – Collection



- A tree is part of a forest.
- A juror is part of a jury.
- This ship is part of a fleet.

Do not confuse with class – member relationships, such as

- The Nile is a river.
- Fido is a dog.

which are not part-of relationships.

**class membership: determined on the basis of similarity to other members.**

**member – collection: determined on the basis of spatial proximity or by social connection.**

# Portion – Mass



- This slice is part of a pie.
- A yard is part of a mile.
- This hunk is part of my clay.

**Homeomeric: Every portion of a pie is “pie”.  
(while, e.g., a window is quite unlike the house of which it is part.)**



Can be distinguished from component – integral object by substituting the phrase “some of”:

- She asked me for part of my orange. (... for some of my orange)

However *\*not\**: The engine is some of the car.

This test won't distinguish from member – collection:

- Some of the fraternity brothers are sophomores.  
(this is the “count” sense of “some”, not the “mass” sense)

However, for member – collection we can phrase it as:

- One of the brothers is a sophomore.

# Stuff – Object



- A martini is partly alcohol.
- The bike is partly steel.
- Water is partly hydrogen.

By asking for: “What is it made of?”

(For component – integral object we would ask:  
“What are its parts?”)

Stuff cannot be separated from the object.

- **Paying is part of shopping.**
- **Bidding is part of playing Bridge.**
- **Ovulation is part of the menstrual cycle.**
- **Dating is part of adolescence.**

**Features or phases of activities and processes.**

**Unlike the other types, in this case we cannot say “X has Y”, such as for others in**

- **Sororities have members.**
- **Bicycles have pedals**
- **Plays have acts.**

**E.g. we cannot say “Shopping has paying”.**

# Place – Area



- The Everglades are part of Florida.
- An oasis is a part of a desert.
- The baseline is part of a tennis court.

# Other apparently similar relations which are not meronymic



- **Topological Inclusion**
  - The wine is in the cooler.
  - The meeting is in the morning.
  - Careful: “The Everglades are part of Florida” is meronymic. But “West Berlin is part of East Germany” is wrong. [Note paper was written 1987.]
- **Class Inclusion**
  - Cars are a type of vehicle.
  - Theft is a crime.
  - Careful: “Frying is a type of cooking” is meronymic, as is “Honesty is a type of virtue”.

# Other apparently similar relations which are not meronymic



- **Attribution**
  - Towers are tall.
  - Coal burns.
  - The joke was funny.
- **Attachment**
  - Earrings are attached to ears.
  - Fingers are attached to hands.  
(note: they are also parts of hands)
- **Ownership**
  - A millionaire has money.
  - The author has the copyright.
  - Jenny has a bicycle.

# Transitivity again



**Simpson's finger is part of Simpson's hand.  
Simpson's hand is part of Simpson's body.  
Simpson's finger is part of Simpson's body.**

**This works, but the following doesn't:**

**Simpson's arm is part of Simpson.  
Simpson is part of the Philosophy Department.  
Hence(?) Simpson's arm is part of the Philosophy Department.**

**Winston argues: If we combine two sentences with the same type of meronymic relation, then we have transitivity.  
Indeed, in all mixed cases, counterexamples to transitivity can be found (given in the paper).**

# Other properties – and some OWL modeling



Winston et al. list several properties of meronymic relations.

First some notation for the 6 types of part-of relations:

- po-component
- po-member
- po-portion
- po-stuff
- po-feature
- po-place

PO is the set containing these six binary relations.

- part-of: The “general” part-whole relation.
- spatially-located-in: topological located-in relationship



# Axioms (extracted from Winston et al.)



1. For all  $R \in PO$ ,  $R$  is transitive, asymmetric, and irreflexive (i.e., a strict partial order).
2. For all  $R \in PO$ ,  $R \sqsubseteq$  part-of.  
Does not imply transitivity of part-of.
3. spatially-located-in is transitive and reflexive.
4. For all  $R \in PO$ , we have
  - $R \circ$  spatially-located-in  $\sqsubseteq$  spatially-located-in
  - spatially-located-in  $\circ R \sqsubseteq$  spatially-located-in
5. For all  $R \in PO \cup \{\text{spatially-located-in}\}$  and all classes  $C$ , we have  $(\forall x)(\forall y)(R(x,y) \wedge C(y) \rightarrow (\exists z)(R(x,z) \wedge C(z)))$ .
6. For all  $R \in PO \cup \{\text{spatially-located-in}\}$  and all classes  $C$ , we have  $(\forall x)(\forall y)(C(y) \wedge (C(y) \rightarrow R(x,y)) \rightarrow R(x,y))$ .

Note: 5+6 are tautologies, so need not be modeled in OWL.

1. For all  $R \in PO$ ,  $R$  is transitive, asymmetric, and irreflexive (i.e., a strict partial order).
2. For all  $R \in PO$ ,  $R \sqsubseteq \text{part-of}$ .  
Does not imply transitivity of part-of.
3. **spatially-located-in** is transitive and reflexive.
4. For all  $R \in PO$ , we have
  - $R \circ \text{spatially-located-in} \sqsubseteq \text{spatially-located-in}$
  - $\text{spatially-located-in} \circ R \sqsubseteq \text{spatially-located-in}$

This results in a total of  $36+26+2+62 = 44$  axioms, all expressible in OWL 2.

However, there is a catch!

1. For all  $R \in PO$ ,  $R$  is transitive, asymmetric, and irreflexive (i.e., a strict partial order).

**Problem: A relation in OWL 2 DL cannot be transitive and reflexive at the same time:**

**A transitive property is complex, and thus not simple. However only simple properties are allowed to be irreflexive.**

**So: this ends up in OWL 2 Full.**

**Straightforward fix:**

**Drop irreflexivity. This will probably work in most cases.**

**Better fixes are based on rules or nominal schemas (covered later in class).**

# Another two catches



**All properties occurring in the above given part-of ontology are complex (i.e., non-simple).**

**OWL 2 has global restrictions on the use of such properties.**

**This hampers modeling, and may yield to OWL 2 Full ontologies after all desired relationships have been modeled.**

**Another problem: Regularity conditions may become violated if merging the part-of ontology with a domain ontology.**

**Fixes: as above (drop some axioms)**

**Better: rules or nominal schemas (covered later in class).**

# Addressing the issues



We have several issues with modeling the part-of ontology following Winston.

E.g., relations cannot be transitive, asymmetric, and irreflexive at the same time.

We can now approximate this as follows:

Characterize the relation (e.g., R) as transitive and asymmetric.

Furthermore, specify  $\{x\} \sqcap \exists R.\{x\} \sqsubseteq \perp$ .

More generally, if you run into a rule which you cannot model in OWL, simply approximate using nominal schemas.

# References



- **Pascal Hitzler, Krzysztof Janowicz, Linked Data, Big Data, and the 4th Paradigm. *Semantic Web* 4 (3), 2013, 233-235.**
- **Krzysztof Janowicz, Pascal Hitzler, The Digital Earth as Knowledge Engine. *Semantic Web* 3 (3), 213-221, 2012.**
- **Gary Berg-Cross, Isabel Cruz, Mike Dean, Tim Finin, Mark Gahegan, Pascal Hitzler, Hook Hua, Krzysztof Janowicz, Naicong Li, Philip Murphy, Bryce Nordgren, Leo Obrst, Mark Schildhauer, Amit Sheth, Krishna Sinha, Anne Thessen, Nancy Wiegand, Ilya Zaslavsky, Semantics and Ontologies for EarthCube. In: K. Janowicz, C. Kessler, T. Kauppinen, D. Kolas, S. Scheider (eds.), *Workshop on GIScience in the Big Data Age, In conjunction with the seventh International Conference on Geographic Information Science 2012 (GIScience 2012)*, Columbus, Ohio, USA. September 18th, 2012. *Proceedings*.**
- **Krzysztof Janowicz, Pascal Hitzler, Thoughts on the Complex Relation Between Linked Data, Semantic Annotations, and Ontologies. In: *Proceedings of the CIKM 2013 Workshop on Exploiting Semantic Annotation, ESAIR 2013*. To appear.**

# References



- **Pascal Hitzler, Frank van Harmelen, A reasonable Semantic Web. Semantic Web 1 (1-2), 39-44, 2010.**
- **Prateek Jain, Pascal Hitzler, Peter Z. Yeh, Kunal Verma, Amit P. Sheth, Linked Data is Merely More Data. In: Dan Brickley, Vinay K. Chaudhri, Harry Halpin, Deborah McGuinness: Linked Data Meets Artificial Intelligence. Technical Report SS-10-07, AAAI Press, Menlo Park, California, 2010, pp. 82-86. ISBN 978-1-57735-461-1. Proceedings of LinkedAI at the AAAI Spring Symposium, March 2010.**
- **Amit Krishna Joshi, Prateek Jain, Pascal Hitzler, Peter Z. Yeh, Kunal Verma, Amit P. Sheth, Mariana Damova, Alignment-based Querying of Linked Open Data. In: Meersman, R.; Panetto, H.; Dillon, T.; Rinderle-Ma, S.; Dadam, P.; Zhou, X.; Pearson, S.; Ferscha, A.; Bergamaschi, S.; Cruz, I.F. (eds.), On the Move to Meaningful Internet Systems: OTM 2012, Confederated International Conferences: CoopIS, DOA-SVI, and ODBASE 2012, Rome, Italy, September 10-14, 2012, Proceedings, Part II. Lecture Notes in Computer Science Vol. 7566, Springer, Heidelberg, 2012, pp. 807-824.**
- **Yingjie Hu, Krzysztof Janowicz, David Carral, Simon Scheider, Werner Kuhn, Gary Berg-Cross, Pascal Hitzler, Mike Dean, A Geo-Ontology Design Pattern for Semantic Trajectories. In: Thora Tenbrink, John G. Stell, Antony Galton, Zena Wood (Eds.): Spatial Information Theory - 11th International Conference, COSIT 2013, Scarborough, UK, September 2-6, 2013. Proceedings. Lecture Notes in Computer Science Vol. 8116, Springer, 2013, pp. 438-456.**

# References



- **David Carral Martinez, Krzysztof Janowicz, Pascal Hitzler, A Logical Geo-Ontology Design Pattern for Quantifying over Types. In: Isabel F. Cruz, Craig Knoblock, Peer Kröger, Egemen Tanin, Peter Widmayer (Eds.): SIGSPATIAL 2012 International Conference on Advances in Geographic Information Systems (formerly known as GIS), SIGSPATIAL'12, Redondo Beach, CA, USA, November 7-9, 2012. ACM 2012, pp. 239-248.**
- **David Carral, Simon Scheider, Krzysztof Janowicz, Charles Vardeman, Adila A. Krisnadhi, Pascal Hitzler, An Ontology Design Pattern for Cartographic Map Scaling. In: Philipp Cimiano, Oscar Corcho, Valentina Presutti, Laura Hollink, Sebastian Rudolph (Eds.), The Semantic Web: Semantics and Big Data. 10th International Conference, ESWC 2013, Montpellier, France, May 26-30, 2013. Proceedings. Lecture Notes in Computer Science Vol. 7882, Springer, Heidelberg, 2013, pp. 76-93.**
- **Prateek Jain, Pascal Hitzler, Kunal Verma, Peter Yeh, Amit Sheth, Moving beyond sameAs with PLATO: Parontology detection for Linked Data. In: Ethan V. Munson, Markus Strohmaier (Eds.): 23rd ACM Conference on Hypertext and Social Media, HT '12, Milwaukee, WI, USA, June 25-28, 2012. ACM, 2012, pp. 33-42.**



# References



- **Piero A. Bonatti, Carsten Lutz, Frank Wolter: The Complexity of Circumscription in DLs. J. Artif. Intell. Res. (JAIR) 35: 717-773 (2009)**
- **Kunal Sengupta, Adila Krisnadhi, Pascal Hitzler, Local Closed World Reasoning: Grounded Circumscription for OWL. In: L. Aroyo, C. Welty, H. Alani, J. Taylor, A. Bernstein, L. Kagal, N. F. Noy, E. Blomqvist (Eds.): The Semantic Web – ISWC 2011 - 10th International Semantic Web Conference, Bonn, Germany, October 23-27, 2011, Proceedings, Part I. Lecture Notes in Computer Science Vol. 7031, Springer, Heidelberg, 2011, pp. 617-632.**
- **Markus Krötzsch, Frederick Maier, Adila Alfa Krisnadhi, Pascal Hitzler, A Better Uncle For OWL – Nominal Schemas for Integrating Rules and Ontologies. In: S. Sadagopan, Krithi Ramamritham, Arun Kumar, M.P. Ravindra, Elisa Bertino, Ravi Kumar (eds.), WWW '11 20th International World Wide Web Conference, Hyderabad, India, March/April 2011. ACM, New York, 2011, pp. 645-654.**